

## Certificate of analysis

### Test of Bitumen grade of 60/70

**Report: ACC 583****Manufacturer: Aras Petrochemical Co****Sample No: 2632022****Source: Aras Petrochemical Co****BITUMEN GRADE 60/70****SPECIFICATION**

PENETRATION AT 25 DEG C, 100 g, 5 Sec

SOFTENING POINT DEG C

DUCTILITY AT 25 DEG C CMS

LOSS ON HEATING PCT WT

FLASH POINT (Cleveland open cup)

SOLUBILITY IN CS<sub>2</sub> PCT WTORGANIC MATTER INSOLUBLE IN CS<sub>2</sub> PCT WT

SPOT TEST

**TEST METHOD**

60/70

49/56

100 MIN

0.2 MAX

250 MIN

99.5 MIN

52 MIN

NEGATIVE

**A.S.T.M.**

D.5

D.36

D.113

D.6

D.92

D2042

D.1754

\*A.A.S.H.O T102-42

**UNITE**

0.1mm

c°

cm

%

c°

%WT

%

1. The test result provided from sample of Aras Petrochemical Co, factory.
2. This report provide for exclusive use of Aras Petrochemical Co, clients.
3. Any copy of this report can be made without client permission.

**PETRO-ACC**  
Aras Petro Chemical co